


MATERIAL SAFETY DATA SHEET



PRODUCT NAME: **Dura-Lastic "SOFT"**

SECTION I - IDENTIFICATION

PERSONAL PROTECTION (SECTION VIII)

HMIS HAZARD RATING
LEAST---0 Slight---1
MODERATE---2 HIGH---3
EXTREME---4

NAME: Silvertree Products, LLC

ADDRESS: 5120 Investment Drive, Fort Wayne, In 46808

INFORMATION PHONE: 260-482-2474

DATE REVISED: MARCH 2004

EMERGENCY CONTACT (CHEMTREC): 800-424-9300

SECTION I - HAZARDOUS INGREDIENTS/SARA I INFORMATION

HAZARDOUS COMPONENTS	CAS NUMBER	OSHA PEL ACGIH TLV MFG TLV	VAPOR PRESSURE mm Hg @ TEMP
*TOLUENE DIISOCYANATE (T.D.I)	26471-62-5 (STEL-.02 ppm)	.005 ppm .005 ppm	0.025
URETHANE PREPOLYMER		N/E N/E	
CRYSTALLINE SILICA (QUARTZ)	14808-60-7	0.1 mg/m ³ 0.1 mg/m ³	

* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372. Information concerning non-hazardous ingredients is considered a Trade Secret.

SECTION I - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: >163°C(325°F)

SPECIFIC GRAVITY: (H₂O=1):1.044

COATING V.O.C: 120 g/l (0.85 lb/gal)

VAPOR DENSITY: HEAVIER THAN AIR

EVAPORATION RATE: SLOWER THAN ETHER

SOLUBILITY IN WATER: REACTS WITH WATER

APPEARANCE AND ODOR: VISCOUS LIQUID. MILD CHEMICAL ODOR

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: > 93°F (200°F)

METHOD USED: PMCC

FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: N/E

UPPER: N/E

EXTINGUISHING MEDIA: DRY CHEMICAL, FOAM, CARBON DIOXIDE. IF WATER IS USED, USE VARY LARGE QUANTITIES OF COLD WATER. THE REACTION BETWEEN WATER AND HOT ISOCYANATE MAY BE VIGOROUS.

SPECIAL FIRE FIGHTING PROCEDURES: WEAR NIOSH APPROVED SELF CONTAINED BREATHING APPARATUS IN POSITIVE PRESSURE MODE WITH FULL FACE PIECE. BOOTS, GLOVES (NEOPRENE), GOGGLES, AND FULL PROTECTIVE CLOTHING ARE ALSO REQUIRED. EXCESSIVE PRESSURE OR TEMPERATURE MAY CAUSE EXPLOSIVE RUPTURE OF CONTAINERS.

UNUSUAL FIRE AND EXPLOSION HAZARDS: WATER CONTAMINATION WILL PRODUCE CARBON DIOXIDE. DO NOT RESEAL CONTAMINATED CONTAINERS AS PRESSURE BUILDUP MAY RUPTURE THEM.

SECTION V - REACTIVITY DATA

STABILITY: STABLE UNDER NORMAL CONDITIONS

CONDITIONS TO AVOID: HIGH TEMPERATURE, OPEN FLAME, AND MOISTURE. CONTACT WITH INCOMPATIBLE MATERIALS IN A CLOSED SYSTEM WILL CAUSE LIBERATION OF CARBON DIOXIDE AND BUILDUP OF PRESSURE.

INCOMPATIBILITY (MATERIALS TO AVOID): THIS PRODUCT WILL REACT WITH ANY MATERIAL CONTAINING ACTIVE HYDROGENS, SUCH AS WATER, ALCOHOL, AMMONIA, AMINES, ALKALIS AND ACIDS. THE REACTION WITH WATER IS VERY SLOW UNDER 50°C. BUT IS ACCELERATED AT HIGHER TEMPERATURE AND IN THE PRESENCE OF ALKALIS, TERTIARY AMINES, AND METAL COMPOUNDS. SOME REACTIONS CAN BE VIOLENT.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: CARBON DIOXIDE, CARBON MONOXIDE, NITROGEN OXIDES, TRACE AMOUNTS OF HYDROGEN CYANIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR. HIGH TEMPERATURES IN THE PRESENCE OF ALKALIS, TERTIARY AMINES, AND METAL COMPOUNDS WILL ACCELERATE POLYMERIZATION. POSSIBLE EVOLUTION OF CARBON DIOXIDE GAS MAY RUPTURE CLOSED CONTAINERS.

SECTION VI - HEALTH HAZARD DATA

SKIN CONTACT: ISOCYANATES REACT WITH SKIN PROTEIN AND MOISTURE AND CAN CAUSE IRRITATION. PROLONGED CONTACT CAN CAUSE REDDENING, SWELLING, RASH, SCALING, BLISTERING, AND, IN SOME CASES SKIN SENSITIZATION. INDIVIDUALS WHO HAVE DEVELOPED A SKIN SENSITIZATION CAN DEVELOP THESE SYMPTOMS AS A RESULT OF CONTACT WITH VERY SMALL AMOUNTS OF LIQUID MATERIAL OR AS A RESULT OF EXPOSURE TO VAPOR.

EYE CONTACT: LIQUID, AEROSOLS OR VAPORS ARE SEVERELY IRRITATING AND CAN CAUSE PAIN, TEARING, REDDENING AND SWELLING. PROLONGED VAPOR CONTACT MAY CAUSE CONJUNCTIVITIS. ANY LEVEL OF CONTACT SHOULD NOT BE LEFT UNTREATED.

SKIN ABSORPTION: SYSTEMICALLY TOXIC CONCENTRATIONS OF THIS PRODUCT WILL PROBABLY NOT BE ABSORBED THROUGH HUMAN SKIN.

INGESTION: CAN RESULT IN IRRITATING AND CORROSIVE ACTION IN THE MOUTH, STOMACH TISSUE AND DIGESTIVE TRACT. SYMPTOMS CAN INCLUDE SORE THROAT, ABDOMINAL PAIN, NAUSEA, VOMITING AND DIARRHEA. SMALL AMOUNTS OF THIS PRODUCT ASPIRATED INTO THE RESPIRATORY SYSTEM DURING INGESTION OR VOMITING MAY CAUSE MILD TO SEVERE PULMONARY INJURY.

INHALATION: TDI VAPORS OR MIST AT CONCENTRATIONS ABOVE THE TLV CAN IRRITATE (BURNING SENSATION) THE MUCOUS MEMBRANES IN THE RESPIRATORY TRACT (NOSE, THROAT, LUNGS) CAUSING RUNNY NOSE, SORE THROAT, COUGHING, CHEST DISCOMFORT, SHORTNESS OF BREATH AND REDUCED LUNG FUNCTION (BREATHING OBSTRUCTION). HIGH VAPOR CONCENTRATIONS MAY CAUSE HEADACHES, DIZZINESS, ANESTHESIA, DROWSINESS, UNCONSCIOUSNESS, AND OTHER CENTRAL NERVOUS SYSTEM (CNS) EFFECTS. PERSONS WITH A PREEXISTING, NONSPECIFIC BRONCHIAL HYPERACTIVITY CAN RESPOND TO CONCENTRATIONS BELOW THE TLV WITH SIMILAR SYMPTOMS AS WELL AS ASTHMA ATTACK. EXPOSURE WELL ABOVE THE TLV MAY LEAD TO BRONCHITIS, BRONCHIAL SPASM AND PULMONARY EDEMA (FLUID IN LUNGS). AS A RESULT OF PREVIOUS REPEATED OVEREXPOSURE OR A SINGLE LARGE DOSE, CERTAIN INDIVIDUALS MAY DEVELOP ISOCYANATE SENSITIZATION (CHEMICAL ASTHMA) WHICH WILL CAUSE THEM TO REACT TO A LATER EXPOSURE TO ISOCYANATE AT LEVELS WELL BELOW THE TLV. SIMILAR TO MANY NON-SPECIFIC ASTHMATIC RESPONSES, THERE ARE REPORTS THAT ONCE SENSITIZED AN INDIVIDUAL CAN EXPERIENCE THESE SYMPTOMS UPON EXPOSURE TO DUST, COLD AIR OR OTHER IRRITANT. THIS INCREASED LUNG SENSITIVITY CAN PERSIST FOR WEEKS AND IN SEVERE CASES FOR SEVERAL YEARS. CHRONIC OVEREXPOSURE TO ISOCYANATE HAS ALSO BEEN REPORTED TO CAUSE LUNG DAMAGE (INCLUDING DECREASE IN LUNG FUNCTION) WHICH MAY BE PERMANENT. SENSITIZATION CAN EITHER BE TEMPORARY OR PERMANENT.

HEALTH HAZARDS: ACUTE: EXPOSURE MAY CAUSE MUCOUS MEMBRANE AND RESPIRATORY TRACT IRRITATION, TIGHTNESS OF CHEST, HEADACHE, SHORTNESS OF BREATH, AND A DRY COUGH. AT CONCENTRATIONS EXCEEDING CURRENT OCCUPATIONAL LIMITS AND FOR SENSITIZED INDIVIDUALS AT LEVELS LESS THAN OR GREATER THAN CURRENT OCCUPATIONAL LIMITS, ASTHMA-LIKE SYMPTOMS MAY OCCUR. THESE SYMPTOMS MAY INCLUDE COUGHING, WHEEZING, AND SHORTNESS OF BREATH. A HYPERSENSITIVE PNEUMONITIS MAY ALSO OCCUR IF THE PERSON IS SENSITIZED. FEVER, NONPRODUCTIVE COUGH, WHEEZING, CHILLS, AND SHORTNESS OF BREATH CHARACTERIZE THIS SYNDROME. DIZZINESS, ANESTHESIA, DROWSINESS, UNCONSCIOUSNESS AND OTHER CENTRAL NERVOUS SYSTEM EFFECTS MAY ALSO RESULT. THE EFFECTS OF ACUTE EXPOSURE MAY BE DELAYED IN ONSET UP TO 12-24 HOURS. **CHRONIC:** REPEATED EXPOSURE ABOVE CURRENT OCCUPATIONAL LIMITS MAY CAUSE AN ALLERGIC SENSITIZATION OF THE RESPIRATORY TRACT. THIS IS CHARACTERIZED BY AN ASTHMA-LIKE RESPONSE UPON RE-EXPOSURE TO THE CHEMICAL. THE SYMPTOMS MAY INCLUDE COUGHING, WHEEZING, SHORTNESS OF BREATH AND CHEST TIGHTNESS. CENTRAL NERVOUS SYSTEM (CNS) IMPAIRMENT POSSIBLY LEADING TO UNCONSCIOUSNESS.

CARCINOGENICITY: NTP: YES IARC MONOGRAPHS: YES OSHA REGULATED: NO
NTP: THE NATIONAL TOXICOLOGY PROGRAM REPORTED THAT TDI CAUSED AN INCREASE IN THE NUMBER OF TUMORS IN EXPOSED RATS OVER THOSE COUNTED IN NON-EXPOSED RATS. THE TDI WAS ADMINISTERED IN CORN OIL AND INTRODUCED INTO THE STOMACH THROUGH A TUBE. BASED ON THIS STUDY, THE NTP HAS LISTED TDI AS A SUBSTANCE THAT MAY REASONABLY BE ANTICIPATED TO BE A CARCINOGEN.

IARC: IARC HAS ANNOUNCED THAT IT WILL LIST TDI AS A SUBSTANCE FOR WHICH THERE IS SUFFICIENT EVIDENCE FOR ITS CARCINOGENICITY IN EXPERIMENTAL ANIMALS BUT INADEQUATE EVIDENCE FOR THE CARCINOGENICITY OF TDI TO HUMANS (IARC MONOGRAPH 39).

INHALATION OF CRYSTALLINE SILICA CAN CAUSE CANCER BASED ON ANIMAL DATA AND IARC CONCLUDES SUFFICIENT EVIDENCE IN HUMANS (GROUP 1). PROLONGED AND REPEATED OVEREXPOSURE TO FREE CRYSTALLINE SILICA DUST ABOVE THE TLV LEVEL MAY CAUSE SCARRING OF THE LUNGS WITH COUGH AND SHORTNESS OF BREATH. SILICOSIS MAY RESULT FROM BREATHING CRYSTALLINE SILICA. SILICA AND OTHER FILLERS ARE ENCAPSULATED AND NOT EXPECTED TO BE RELEASED FROM PRODUCT UNDER NORMAL CONDITIONS OF USE.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: CARDIOVASCULAR DISEASE, ASTHMA OR ASTHMATIC BRONCHITIS, EMPHYSEMA, ALLERGIC DISEASE, CHRONIC RESPIRATORY DISEASE, SINUSITIS, HEADACHE AND DIZZINESS.

EMERGENCY AND FIRST AID PROCEDURES: EYE CONTACT: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER, PREFERABLY LUKEWARM. AFTER INITIAL FLUSHING, REMOVE ANY CONTACT LENSES AND CONTINUE FLUSHING FOR AT LEAST 15 MINUTES. HAVE EYES EXAMINED AND TREATED BY MEDICAL PERSONNEL. **INHALATION:** REMOVE VICTIM TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH. IF BREATHING IS LABORED, GIVE OXYGEN. CONSULT MEDICAL PERSONNEL. **SKIN CONTACT:** WASH MATERIAL OFF OF THE SKIN WITH PLENTY OF SOAP AND WATER. IF REDNESS, ITCHING, OR A BURNING SENSATION DEVELOPS. GET MEDICAL ATTENTION. WASH CONTAMINATED CLOTHING AND DECONTAMINATE FOOTWEAR BEFORE REUSE. **INGESTION:** DO NOT INDUCE VOMITING. GIVE 1 OR 2 GLASSES OF WATER TO DRINK AND REFER PERSON TO MEDICAL PERSONNEL. (DO NOT GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON).

SECTION VI - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WEAR SKIN, EYE, AND RESPIRATORY PROTECTION DURING CLEANUP. SOAK UP MATERIAL WITH ABSORBENT AND SHOVEL INTO A CHEMICAL WASTE CONTAINER. COVER CONTAINER, BUT DO NOT SEAL, AND REMOVE FROM WORK AREA.

WASTE DISPOSAL METHOD: DISPOSE OF IN COMPLIANCE WITH ALL RELEVANT LOCAL, STATE, AND FEDERAL LAWS AND REGULATIONS REGARDING TREATMENT.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE IN TIGHTLY SEALED CONTAINERS TO PROTECT FROM ATMOSPHERIC MOISTURE. STORE IN A COOL DRY AREA. STORE LIQUID IN CONTAINERS ABOVE GROUND AND SURROUND BY DIKES TO CONTAIN SPILLS OR LEAKS.

OTHER PRECAUTIONS: PREVENT SKIN AND EYE CONTACT. OBSERVE TLV LIMITATIONS. AVOID BREATHING VAPORS. WORKERS SHOULD SHOWER AND CHANGE TO FRESH CLOTHING AFTER EACH SHIFT. A SENSITIZED INDIVIDUAL SHOULD NOT BE EXPOSED TO THE PRODUCT WHICH CAUSED THE SENSITIZATION. AIR CIRCULATION AND EXHAUSTION OF ISOCYANATE VAPORS MUST BE MAINTAINED UNTIL THE COATINGS HAVE FULLY CURED TO INSURE THAT NO POTENTIAL FIRE, EXPLOSION OR HEALTH HAZARD REMAINS. WARNING PROPERTIES (IRRITATION OF THE EYES, NOSE AND THROAT OR ODOR) ARE NOT ADEQUATE TO PREVENT CHRONIC OVEREXPOSURE FROM INHALATION. THIS PRODUCT CAN PRODUCE ASTHMATIC SENSITIZATION UPON EITHER SINGLE INHALATION EXPOSURE TO A RELATIVELY HIGH CONCENTRATION OR UPON REPEATED INHALATION EXPOSURE TO LOWER CONCENTRATIONS. EXPOSURE TO VAPORS OF HEATED ISOCYANATES CAN BE EXTREMELY DANGEROUS. EMPLOYEE EDUCATION AND TRAINING IN SAFE HANDLING OF THIS MATERIAL IS REQUIRED UNDER OSHA HAZARD COMMUNICATION STANDARD. INDIVIDUALS WITH EXISTING RESPIRATORY DISEASE SUCH AS CHRONIC BRONCHITIS, EMPHYSEMA, OR ASTHMA SHOULD NOT BE EXPOSED TO ISOCYANATES. THESE INDIVIDUALS SHOULD BE IDENTIFIED THROUGH BASELINE AND ANNUAL EVALUATION AND REMOVED FROM FURTHER EXPOSURE. MEDICAL EXAMINATION SHOULD INCLUDE MEDICAL HISTORY, VITAL CAPACITY, AND FORCED EXPIRATION VOLUME AT ONE SECOND.

SECTION VII - CONTROL MEASURES

VENTILATION: USE LOCAL EXHAUST VENTILATION TO KEEP AIRBORNE CONCENTRATIONS BELOW THE TLV. FOLLOW GUIDELINES IN THE ACGIH PUBLICATION "INDUSTRIAL VENTILATION".

RESPIRATORY PROTECTION: IF AIRBORNE CONCENTRATIONS EXCEED OR ARE EXPECTED TO EXCEED THE TLV. USE MSHA/NIOSH APPROVED POSITIVE PRESSURE SUPPLIED AIR RESPIRATOR WITH A FULL FACE PIECE OR AN AIR SUPPLIED HOOD. FOR EMERGENCIES, USE A POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS, AIR PURIFYING (CARTRIDGE TYPE) RESPIRATORS ARE NOT APPROVED FOR PROTECTION AGAINST ISOCYANATES.

PROTECTIVE CLOTHING: GLOVES DETERMINED TO BE IMPERVIOUS UNDER THE CONDITIONS OF USE SHOULD BE WORN ALWAYS WHEN WORKING WITH THIS PRODUCT. DEPENDING ON CONDITIONS OF USE, ADDITIONAL PROTECTION MAY BE REQUIRED SUCH AS APRON, ARM COVERS, OR FULL BODY SUIT. WASH CONTAMINATED CLOTHING BEFORE REWEARING. PROTECTIVE CLOTHING SHOULD BE SELECTED AND USED IN ACCORDANCE WITH "GUIDELINES FOR THE SELECTION OF CHEMICAL PROTECTIVE CLOTHING" PUBLISHED BY ACGIH.

EYE PROTECTION: CHEMICAL TIGHT GOGGLES AND FULL FACE SHIELD.

OTHER PROTECTIVE EQUIPMENT AND MEASURES: UNHINDERED ACCESS TO SAFETY SHOWER AND EYE WASH STATIONS. AS A GENERAL HYGIENIC PRACTICE, WASH HANDS AND FACE AFTER USE. SHOWERS AND CLEANING OF CLOTHES ARE RECOMMENDED. FOLLOW ALL LABEL INSTRUCTIONS. EDUCATE AND TRAIN EMPLOYEES IN SAFE USE OF PRODUCT.

SECTION IX-REGULATORY INFORMATION

DOT PROPER SHIPPING NAME: NOT REGULATED.

STATE REGULATIONS: CALIFORNIA - AS PER REQUIREMENTS OF THE SAFE DRINKING WATER & TOXIC ENFORCEMENT ACT OF CA. U.S.A. 1985 (PROPOSITION 65). THE PUBLIC IS WARNED THAT MATERIALS USED IN THIS PRODUCT MAY CREATE AN EXPOSURE TO CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM. THIS WARNING REQUIRED BY SECTION 25249.6 OF THE CALIFORNIA HEALTH AND SAFETY CODE.

TOXIC SUBSTANCE CONTROL ACT: ALL CHEMICALS COMPRISING THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY.

USER'S RESPONSIBILITY: A BULLETIN SUCH AS THIS CANNOT BE EXPECTED TO COVER ALL POSSIBLE INDIVIDUAL SITUATIONS. AS THE USER HAS THE RESPONSIBILITY TO PROVIDE A SAFE WORKPLACE, ALL ASPECTS OF AN INDIVIDUAL OPERATION SHOULD BE EXAMINED TO DETERMINE IF, OR WHERE, PRECAUTIONS, IN ADDITION TO THOSE DESCRIBED HEREIN, ARE REQUIRED. ANY HEALTH HAZARD AND SAFETY INFORMATION HEREIN SHOULD BE PASSED ON TO YOUR CUSTOMERS OR EMPLOYEES, AS THE CASE MAY BE.

DISCLAIMER: THE INFORMATION CONTAINED HEREIN IS, TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ACCURATE AND CURRENT AS OF THE DATE OF THIS MSDS. HOWEVER, SINCE THE CONDITIONS OF HANDLING AND USE ARE BEYOND OUR CONTROL, WE MAKE NO GUARANTEE OF RESULTS, AND ASSUME NO LIABILITY FOR DAMAGES INCURRED BY USE OF THIS MATERIAL. ALL CHEMICALS MAY PRESENT UNKNOWN HEALTH HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS WHICH EXIST. FINAL DETERMINATION OF SUITABILITY OF THE CHEMICAL IS THE SOLE RESPONSIBILITY OF THE USER. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN OR THE CHEMICAL TO WHICH THE INFORMATION REFERS. IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL APPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.