


MATERIAL SAFETY DATA SHEET



PRODUCT NAME: **Dura-Poxy Part B**

SECTION I - IDENTIFICATION

PERSONAL PROTECTION (SECTION VIII)

HMIS HAZARD RATING
LEAST ---- 0 SLIGHT---1
MODERATE---2 HIGH---3
EXTREME---4

NAME: Silvertree Products 5120 Investment Dr Ft. Wayne, In 46808

ADDRESS: 13455 PUMICE STREET, NORWALK, CA 90650 **INFORMATION PHONE:** 260-426-2474

DATE REVISED: MARCH 2005

EMERGENCY CONTACT (CHEMTREC): 800-424-9300

SECTION I - HAZARDOUS INGREDIENTS/SARA I INFORMATION

HAZARDOUS COMPONENTS	OCCUPATIONAL EXPOSURE LIMITS		VAPOR PRESSURE
	CAS NUMBER	OSHA PEL ACGIH TLV MFG TLV	mm Hg @ TEMP
BISPHENOL-A/ EPICHLOROHYDRIN RESIN	25068-38-6	N/E	N/E
ALKYL (C12-C14) GLYCIDYL ETHER	68609-97-2	N/E	N/E

* INDICATES toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372. Information concerning non-hazardous ingredients is considered a Trade Secret.

SECTION I - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: N/A

COATING V.O.C: 90 g/l (0.75 lb/gal)

EVAPORATION RATE: N/A

APPEARANCE AND ODOR: THIN BLUE LIQUID, MILD ODOR

SPECIFIC GRAVITY: (H₂O=1):1.09

VAPOR DENSITY: HEAVIER THAN AIR

SOLUBILITY IN WATER: SLIGHT

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: >93°C (200°F)

METHOD USED: TCC

FLAMMABLE LIMITS IN AIR BY VOLUME - LOWER: N/E

UPPER: N/E

EXTINGUISHING MEDIA: DRY CHEMICAL, FOAM, CARBON DIOXIDE AND WATER FOG.

SPECIAL FIRE FIGHTING PROCEDURES: WEAR NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS IN POSITIVE PRESSURE MODE WITH FULL FACE PIECE. BOOTS, GLOVES (NEOPRENE), GOGGLES AND FULL PROTECTIVE CLOTHING ARE ALSO REQUIRED. EXCESSIVE PRESSURE OR TEMPERATURE MAY CAUSE EXPLOSIVE RUPTURE OF CONTAINERS.

UNUSUAL FIRE AND EXPLOSION HAZARDS: CLOSED CONTAINERS MAY RUPTURE DUE TO VERY HIGH TEMPERATURE OR INDUCED PRESSURE.

SECTION V - REACTIVITY DATA

STABILITY: STABLE UNDER NORMAL CONDITIONS.

CONDITIONS TO AVOID: HEAT, HIGH TEMPERATURE AND OPEN FLAME. CONTACT WITH INCOMPATIBLE MATERIALS IN A CLOSED SYSTEM WILL CAUSE BUILDUP OF PRESSURE.

INCOMPATIBILITY (MATERIALS TO AVOID): THIS PRODUCT WILL REACT WITH MATERIAL SUCH AS AMINES, ALKALIS AND ACIDS. AVOID STRONG OXIDIZING AGENTS. SOME REACTIONS CAN BE VIOLENT.

HAZARDOUS DECOMPOSITION OR BY-PRODUCTS: ORGANIC VAPORS AND OTHER THERMAL DECOMPOSITION PRODUCTS.

SECTION VI - HEALTH HAZARD DATA

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR.

SKIN CONTACT: FREQUENT AND PROLONGED CONTACT CAN CAUSE IRRITATION AND/OR DERMATITIS.

EYE CONTACT: CAN BE MODERATELY IRRITATING TO THE EYES.

SKIN ABSORPTION: SYSTEMICALLY TOXIC CONCENTRATIONS OF THIS PRODUCT WILL PROBABLY NOT BE ABSORBED THROUGH HUMAN SKIN.

INGESTION: IRRITATION OR CHEMICAL BURNS OF THE MOUTH, PHARYNX, ESOPHAGUS AND STOMACH CAN DEVELOP FOLLOWING INGESTION.

INHALATION: VAPORS CAN IRRITATE EYES, NOSE AND RESPIRATORY PASSAGES. OVEREXPOSURE MAY INDUCE HEADACHES, DIZZINESS, DROWSINESS OR UNCONSCIOUSNESS. CHRONIC EXPOSURES MAY RESULT IN PERMANENT DECREASES IN LUNG FUNCTION.

HEALTH HAZARDS: ACUTE: EXPOSURE MAY CAUSE MUCOUS MEMBRANE AND RESPIRATORY TRACT IRRITATION, TIGHTNESS OF CHEST, HEADACHE, SHORTNESS OF BREATH, AND A DRY COUGH. THE EFFECTS OF ACUTE EXPOSURE MAY BE DELAYED IN ONSET UP TO 12-24 HOURS. **CHRONIC:** REPEATED EXPOSURE ABOVE CURRENT OCCUPATIONAL LIMITS MAY CAUSE AN ALLERGIC SENSITIZATION OF THE RESPIRATORY TRACT. THIS IS CHARACTERIZED BY AN ASTHMA-LIKE RESPONSE UPON REEXPOSURE TO THE CHEMICAL. THE SYMPTOMS MAY INCLUDE COUGHING, WHEEZING, SHORTNESS OF BREATH AND CHEST TIGHTNESS.

CARCINOGENICITY: NTP: NO IARC MONOGRAPHS: NO OSHA REGULATED: NO

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: CARDIOVASCULAR DISEASE, ASTHMA OR ASTHMATIC BRONCHITIS, ALLERGIC DISEASE, CHRONIC RESPIRATORY DISEASE, SINUSITIS, HEADACHE AND DIZZINESS.

EMERGENCY AND FIRST AID PROCEDURES: EYE CONTACT: IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER. AFTER INITIAL FLUSHING, REMOVE ANY CONTACT LENSES AND CONTINUE FLUSHING FOR AT LEAST 15 MINUTES. HAVE EYES EXAMINED AND TREATED BY MEDICAL PERSONNEL. **INHALATION:** REMOVE VICTIM TO FRESH AIR. IF NOT BREATHING, GIVE ARTIFICIAL RESPIRATION, PREFERABLY MOUTH-TO-MOUTH. IF BREATHING IS LABORED, GIVE OXYGEN. CONSULT MEDICAL PERSONNEL. **SKIN CONTACT:** WASH MATERIAL OFF OF THE SKIN WITH PLENTY OF SOAP AND WATER. IF REDNESS, ITCHING, OR A BURNING SENSATION DEVELOPS, GET MEDICAL ATTENTION. WASH CONTAMINATED CLOTHING AND DECONTAMINATE FOOTWEAR BEFORE REUSE. **INGESTION:** GIVE 1 OR 2 GLASSES OF WATER AND INDUCE VOMITING. KEEP VICTIM'S HEAD BELOW HIPS WHILE VOMITING TO PREVENT ASPIRATION OF LIQUID INTO THE LUNGS. (NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON).

SECTION VI - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: WEAR SKIN, EYE, AND RESPIRATORY PROTECTION DURING CLEANUP. SOAK UP MATERIAL WITH ABSORBENT AND SHOVEL INTO A CHEMICAL WASTE CONTAINER. COVER CONTAINER, BUT DO NOT SEAL, AND REMOVE FROM WORK AREA. RESIDUES FROM SPILL CLEANUP, MAY CONTINUE TO BE REGULATED UNDER PROVISIONS OF RCRA AND REQUIRE STORAGE AND DISPOSAL AS HAZARDOUS WASTE. FOR MAJOR SPILLS, CALL CHEMTREC (CHEMICAL TRANSPORTATION EMERGENCY CENTER) AT 800-424-9300.

WASTE DISPOSAL METHOD: RESIDUES MAY STILL BE SUBJECT TO RCRA STORAGE AND DISPOSAL REQUIREMENTS. DISPOSE OFF IN COMPLIANCE WITH ALL RELEVANT LOCAL, STATE, AND FEDERAL LAWS AND REGULATIONS REGARDING TREATMENT.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE IN TIGHTLY SEALED CONTAINERS TO PROTECT FROM ATMOSPHERIC MOISTURE. STORE IN A COOL DRY AREA. THE MATERIAL IS COMBUSTIBLE: THE COMBUSTION PRODUCTS MAY BE HAZARDOUS. DO NOT EXPOSE THIS MATERIAL TO OPEN FLAMES.

OTHER PRECAUTIONS: PREVENT SKIN AND EYE CONTACT. OBSERVE TLV LIMITATIONS. AVOID BREATHING VAPORS. WORKERS SHOULD SHOWER AND CHANGE TO FRESH CLOTHING AFTER EACH SHIFT. INDIVIDUALS WITH EXISTING RESPIRATORY DISEASE SUCH AS CHRONIC BRONCHITIS, EMPHYSEMA, OR ASTHMA SHOULD NOT BE EXPOSED. THESE INDIVIDUALS SHOULD BE IDENTIFIED THROUGH BASELINE AND ANNUAL EVALUATION AND REMOVED FROM FURTHER EXPOSURE. MEDICAL EXAMINATION SHOULD INCLUDE MEDICAL HISTORY, VITAL CAPACITY, AND FORCED EXPIRATORY VOLUME AT ONE SECOND.

SECTION VI - CONTROL MEASURES

VENTILATION: USE LOCAL EXHAUST VENTILATION TO KEEP AIRBORNE CONCENTRATIONS BELOW THE TLV. FOLLOW GUIDELINES IN THE ACGIH PUBLICATION "INDUSTRIAL VENTILATION". EXHAUST AIR MAY NEED TO BE CLEANED BY SCRUBBERS OF FILTERS TO REDUCE ENVIRONMENTAL CONTAMINATION.

RESPIRATORY PROTECTION: AVOID BREATHING VAPOR OR MISTS. IF EXPOSURE MAY OR DOES EXCEED OCCUPATIONAL EXPOSURE LIMITS (SEC.II). USE A NIOSH APPROVED RESPIRATOR TO PREVENT OVEREXPOSURE. IN ACCORDANCE WITH 29 CFR 19010.134. USE EITHER AN ATMOSPHERE SUPPLYING RESPIRATOR OR AN AIR-PURIFYING RESPIRATOR FOR ORGANIC VAPORS.

PROTECTIVE CLOTHING: GLOVES DETERMINED TO BE IMPERVIOUS UNDER THE CONDITIONS OF USE SHOULD BE WORN ALWAYS WHEN WORKING WITH THIS PRODUCT. DEPENDING ON CONDITIONS OF USE, ADDITIONAL PROTECTION MAY BE REQUIRED SUCH AS APRON, ARM COVERS, OR FULL BODY SUIT. WASH CONTAMINATED CLOTHING BEFORE REWEARING. PROTECTIVE CLOTHING SHOULD BE SELECTED AND USED IN ACCORDANCE WITH "GUIDELINES FOR THE SELECTION OF CHEMICAL PROTECTIVE CLOTHING" PUBLISHED BYACGIH.

EYE PROTECTION: CHEMICAL TIGHT GOGGLES OR FULL FACE SHIELD.

OTHER PROTECTIVE EQUIPMENT AND MEASURES: UNHINDERED ACCESS TO SAFETY SHOWER AND EYE WASH STATIONS. AS A GENERAL HYGIENIC PRACTICE, WASH HANDS AND FACE AFTER USE. SHOWERS AND CLEANING OF CLOTHES ARE RECOMMENDED.

SECTION IX-REGULATORY INFORMATION
--

DOT PROPER SHIPPING NAME: NOT REGULATED.

STATE REGULATIONS: CALIFORNIA -AS PER REQUIREMENTS OF THE SAFE DRINKING WATER & TOXIC ENFORCEMENTACT OF CA, USA 1985 (PROPOSITION 65), THE PUBLIC IS WARNED THAT MATERIALS USED IN THIS PRODUCT MAY CREATE AN EXPOSURE TO CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS, OR OTHER REPRODUCTIVE HARM. THIS WARNING REQUIRED BY SECTION 25249.6 OF THE CALIFORNIA HEALTH AND SAFETY CODE. TOXIC SUBSTANCE CONTROL ACT: ALL CHEMICALS COMPRISING THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY.

TOXIC SUBSTANCE CONTROL ACT:ALL CHEMICALS COMPRISING THIS PRODUCT ARE LISTED ON THE TSCA INVENTORY.

USER'S RESPONSIBILITY: A BULLETIN SUCH AS THIS CANNOT BE EXPECTED TO COVER ALL POSSIBLE INDIVIDUAL SITUATIONS. AS THE USER HAS THE RESPONSIBILITY TO PROVIDE A SAFE WORKPLACE, ALLASPECTS OF AN INDIVIDUAL OPERATION SHOULD BE EXAMINED TO DETERMINE IF, OR WHERE, PRECAUTIONS, IN ADDITION TO THOSE DESCRIBED HEREIN, ARE REQUIRED. ANY HEALTH HAZARD AND SAFETY INFORMATION HEREIN SHOULD BE PASSED ON TO YOUR CUSTOMERS OR EMPLOYEES, AS THE CASE MAY BE.

DISCLAIMER: THE INFORMATION CONTAINED HEREIN IS, TO THE BEST OF OUR KNOWLEDGE AND BELIEF, ACCURATE AND CURRENT AS THE DATE OF THIS MSDS. HOWEVER, SINCE THE CONDITIONS OF HANDLING AND USE ARE BEYOND OUR CONTROL, WE MAKE TO GUARANTEE OF RESULTS, AND ASSUME NO LIABILITY FOR DAMAGES INCURRED BY USE OF THIS MATERIAL. ALL CHEMICALS MAY PRESENT UNKNOWN HEALTHY HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS WHICH EXIST. FINAL DETERMINATION OF SUITABILITY OF THE CHEMICALS THE SOLE RESPONSIBILITY OF THE USER. NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESSED OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER NATURE ARE MADE HEREUNDER WITH RESPECT TO THE INFORMATION CONTAINED HEREIN OR THE CHEMICAL TO WHICH THE INFORMATION REFERS. IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALLAPPLICABLE FEDERAL, STATE AND LOCAL LAWS AND REGULATIONS.